

In-Wall Timer - Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 15,30,45 Minute,1,2 Hour, Without Hold, Ivory

Item EI235



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- No programming required
- Provides silent operation in time ranges from 15 minutes to 2 hours
- Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- Replaces single-pole switches in a variety of applications
- Incandescent/fluorescent/CFL/LED compatible
- For use with decorator-style wall plate (not included)
- Requires neutral connection

APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation

TECHNICAL DATA

General

Model Number	EI235
Description	Electronic Countdown Timer, 120 VAC, 60 Hz, Preset Times 15,30,45 Minute,1,2 Hour, Without Hold, Ivory
UPC Code	078275111189
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Harmonized Code	9107.00.4080

Control Specifications

Time Presets	15 min; 30 min; 45 min; 1 hr; 2 hrs
Setpoint Program Count	5
Operation Mode	Countdown
Countdown Time	2 hrs
Hold Mode Included	No
Mechanism Type	Digital/Electrical

Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in
-----------------------------------	--------------------------

Material Specifications

Color

Ivory

Load Ratings

Resistive Heater	15 A, 1800 W
Tungsten (Incandescent) Range(s)	1000 W
Ballast Fluorescent	8 A, 1000 VA
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1/4 HP

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes

Environmental Specifications

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

Packaging

Shipping Weight (lbs)	0.4
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

Standards and Certifications

UL Certification	cULus
California Proposition 65	DEHP
PDF Standards And Certifications	cULus