

## Weather Proof Cover - Extra-Duty Plastic In-Use Weatherproof Cover, Double-Gang, Vrt, 3.625" Black

Item WP5240BL



 

### FEATURES

- Complies with 2020 NEC Article 406.9 (B)(1) for wet locations and extra-duty applications
- CEC Article 26-702 Compliant
- UL Certified for Type 3R outdoor enclosures
- Meets requirements for cold impact testing: -60° F (-51° C)
- Heavy-duty UV stabilized polycarbonate cover, mounting base, and inserts
- 1/8" (3 mm) thick, pre-adhered neoprene gasket with slits for mounting screws
- Lockable hasp: All models accept up to 1/4" (6 mm) dia. shank
- Impact rated: 12 lb. impact test to ensure cover remains intact
- Reinforced hinge pin designed to exceed 40 lb. hinge hang/stress test
- Warranty: 1-year limited
- Six inserts provided with all models that allow each model to meet multiple installations (up to 70 configurations)
- Max cord size: (2) #12 AWG or (1) #10 AWG
- 30/50 A (1) #6 AWG

### APPLICATIONS

- Receptacle Protection

### TECHNICAL DATA

#### General

Model Number	WP5240BL
Description	Extra-Duty Plastic In-Use Weatherproof Cover, Double-Gang, Vrt, 3.625" Black
UPC Code	078275145986
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Mechanical Specifications

Number of Included Inserts	6
Insert Types Included	WP217
Hinge Direction	Vertical
Is Extra-Duty Rated	Yes

#### Dimensions

Product Dimensions (H x W x D) in	6 x 6 5/8 x 3 5/8 in
Accepted Cord Size Max	2x12 AWG; 1x10 AWG
Box Type	Double

#### Material Specifications

Color	Black
Weatherproof Cover Material	UV Stabilized Plastic

#### Packaging

Shipping Weight (lbs)	0.75
Unit Carton Dimensions (H x W x L) in	6.5 x 2.75 x 6.5 in

**Standards and Certifications**

UL Certification	cULus
CSA Certification	cCSAus
California Proposition 65	None

---

## ACCESSORIES



WP217

Double-Gang Inserts (6)