

Photocontrol - NightFox™ Select Grade Locking Type Electronic Photocontrol, 120-277 V, Mexico Sales Only

Item EK4536MX

**NOM**

PRODUCT DESCRIPTION

Designed to meet a 15-year service life, this photocontrol is LED-compatible and backed by an 8-year warranty.

FEATURES

- ▶ Non-drift silicon light sensor with IR filter
- ▶ DC relay with zero-crossing circuitry for extended life
- ▶ All components meet 15-year life expectancy
- ▶ Conformal coated PCB
- ▶ Exceeds 10,000 ON/OFF switching cycles
- ▶ Ideal for single or multifixture HID and LED installations (up to 1,650 W @ 277 VAC)
- ▶ 510 J MOV surge protection
- ▶ High precision, microprocessor-controlled zero-cross switching, individually calibrated to extend the life of 20 A relay independent of load being switched

APPLICATIONS

- ▶ Outdoor Lighting Control

TECHNICAL DATA

General

Model Number	EK4536MX
Description	NightFox™ Select Grade Locking Type Electronic Photocontrol, 120-277 V, Mexico Sales Only
UPC Code	078275130173
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	8-Year limited
Usage Environments	Outdoor
Photocontrol Type	Electronic
Expected Lifetime (Years)	15
Expected Lifetime (Operations)	10000
Application Compatibilities	LED; Incandescent; HID
Photocontrol Style	Locking type
Photocontrol Sensor Location	Side

Control Specifications

Sensor Time Delay	Instant ON; 2 sec to 5 sec OFF
Photozell Type	Silicon Diode
Photo Control Switch Type	Relay
Fail Mode	ON
Activation On	1.5 fc
Activation Off	2.25 fc

Dimensions

Product Height (in)	2 3/4
Product Height (mm)	69.9
Product Diameter (in)	3.375

Product Diameter (mm)	85.8
-----------------------	------

Material Specifications

Cover Color	White with Blue Band
Housing Material	Polypropylene

Load Ratings

Magnetic Ballast Range(s)	1800 VA
Tungsten Range(s)	1000 W
Electronic Ballast Load Ratings Ranges	6 A, 120-277 VAC, 50/60 Hz

Electrical Specifications

Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Surge Protection Technology	510 J MOV

Packaging

Shipping Weight (lbs)	0.299
Unit Carton Dimensions (H x W x D) in	3.25 x 3.19 x 3.19 in

Environmental Specifications

Temperature (operation)	-40°C..70°C
-------------------------	-------------

Standards and Certifications

UL Certification	cULus
Other Certifications and Compatibilities	NOM; Ansi C136.10
California Proposition 65	None

ACCESSORIES



K171H
 Locking Type Receptacle, 7-Pin, C136.41
 Compliant, 12" lead



K121
 Locking Type Receptacle, 3-Pin, C136.10
 Compliant, 9" lead



K122
 Locking Type Receptacle, 3-Pin, C136.10
 Compliant, with Pole Mounting Bracket



K121-30
 Locking Type Receptacle, 3-Pin, C136.10
 Compliant, 30" lead



KPT0170-010
 PowerTap Receptacle, 7-Pin, C136.41
 Compliant, Always-On, 10' cable



KPT1170-010
 PowerTap Receptacle, 7-Pin, C136.41
 Compliant, Dusk-to-Dawn, 10' cable



SK4500K
 Shorting Plug for Locking Type Receptacles



KPT0170-015
 PowerTap Receptacle, 7-Pin, C136.41
 Compliant, Always-On, 15' cable