

GR_Analog Time Switches - Electromechanical Synchronous clock, 24-Hour, 220-240 VAC, 50 Hz, Surface Mount Timer Module with Manual Override, 15 Minute Intervals, 16 A, SPDT, Black housing - TCC 111.2 180

Item 017900301 / EAN-Code 1220000331563



PRODUCT DESCRIPTION

The universal time switches from the TCC product family offer versatility in the entire building and in the outdoor area. They are used in switching systems, in machine control systems, as well as specific solutions such as swimming pools or sprinkler systems. The analogue 1-channel universal time switches of the TCC series are suitable for assembly, installation and DIN rail mounting, are easy to operate and are equipped with a quartz or synchronous drive.

FEATURES

- 16 A, 250 VAC SPDT switch
- Synchronous drive
- Captive tripper levers with 15 minute intervals
- Manual override, ON-AUTO-OFF
- Easy set, true clock face
- Surface, DIN rail or flush mounting
- Clear plastic dust cover
- Compact size

APPLICATIONS

- Air Movement & Ventilation
- Distribution/Control Panel
- Distribution Panel
- Indoor Lighting Control
- Landscape Lighting
- Landscape Water Control
- Machinery & Pump Controls
- Motor Control
- Outdoor Lighting Control
- Outdoor Water Fountains
- Pool Pump
- Pump Control
- Septic Treatment
- Timing/Scheduling ON/OFF

TECHNICAL DATA

General

Model Number	017900301
Description	Electromechanical Synchronous clock, 24-Hour, 220-240 VAC, 50 Hz, Surface Mount Timer Module with Manual Override, 15 Minute Intervals, 16 A, SPDT, Black housing - TCC 111.2 180
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year
Harmonized Code	9107.00.8000
EAN Code	1220000331563

Control Specifications

Clock Drive Type	Synchronous
Mechanism Type	Analog/Mechanical

Dimensions

Product Dimensions (H x W x D) mm	80 x 72 x 55 mm
Product Dimensions (H x W x D) in	3.14 x 2.83 x 2.165 in
Material Specifications	
Color	Gray
Load Ratings	
Resistive	16 A, 250 VAC, 21 A
Inductive	8 A, 250 VAC
Electrical Specifications	
Input Voltage Range(s)	220-240 VAC
Accuracy	Mains synchronized
Current Output	Changeover, Potential-free
Load incandescent bulb	1300 W
Input Voltage Frequencies	50 Hz
Display and Format	
Shortest switching time	ON/OFF 15 minutes
Packaging	
Shipping Weight (kg)	0.098
Shipping Weight (lbs)	0.217
Product Weight (kg)	0.098
Product Weight (lbs)	0.216
Unit Carton Dimensions (H x W x D) in	1.482 x 2.867 x 2.867 in
Units Per Pallet	999
Operating Specifications	
Channels	1
Manual switch	Automatic Mode; Fix ON/OFF
Program	Daily Program (ON/OFF)
Environmental Specifications	
Temperature (operation)	-20 - 55 °C / -4 - 131 °F
Standards and Certifications	
Other Certifications and Compatibilities	CE; REACH
RoHS Certification	Yes

ACCESSORIES

**Product
Image
Not
Available**

014500176

Seal, TCC Series