

Mechanical Time Switch - 24-Hour 208-277V Mechanical Panel Mount Timer with Manual Override, 48 Trippers

Item PB914N66



PRODUCT DESCRIPTION

These timers provide automatic control for pumps, cleaners and other types of loads. Timers have three-way mounting; flush in round opening, raised in rectangular opening or on base. Quick connect terminals for easy installation.

FEATURES

- ▶ Automated control for pumps, cleaners and other types of loads
- ▶ 3 different mounting methods
- ▶ Quick connect terminals for easy installation
- ▶ 24-hour timing cycle - MIN ON time 1-hr, MAX ON time 23-hr, 30-min intervals
- ▶ 7-day timing cycle - 6 to 162-hr ON time, 3-hr intervals

Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

APPLICATIONS

- ▶ Motor Control
- ▶ Pump Control

TECHNICAL DATA

Control Specifications

| | |
|---------------------|---------|
| Operation Mode | 24 hour |
| Has Manual Override | Yes |

Dimensions

| | |
|--------------------|-------|
| Product Width (in) | 2.813 |
|--------------------|-------|

Electrical Specifications

| | |
|------------------------|---|
| Wiring Option | Terminals; (4) 1/4" male (2) for load (2) for independent clock motor |
| Input Voltage Range(s) | 208-277 VAC, 60 Hz |
| Number of Circuits | 1 |
| Switch Type | SPST |

General

| | |
|--------------------------------|---|
| Model Number | PB914N66 |
| Description | 24-Hour 208-277V Mechanical Panel Mount Timer with Manual Override, 48 Trippers |
| UPC Code | 099999999990 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 1-Year limited |

Load Ratings

| | |
|--------------------------------|--|
| Motor | 1 HP, 16 FLA @ 120 VAC, 60 Hz; 2 HP, 12 FLA @ 240 VAC, 60 Hz |
| Resistive Load Ratings Ranges | 20 A, 120-277 VAC, 60 Hz |
| Pilot Duty Load Ratings Ranges | 360 VA, 120-240 VAC, 60 Hz |

Mechanical Specifications

| | |
|------------------|----|
| Captive Trippers | 48 |
|------------------|----|

Packaging

| | |
|-------------------------|-------|
| Shipping Weight (lbs) | 0.351 |
| Unit Carton Height (in) | 4 |

Standards and Certifications

| | |
|--|------|
| Other Certifications and Compatibilities | RU |
| California Proposition 65 | None |

ACCESSORIES



156PB10398A

Trippers - Clip, ON/OFF, 24-Hr for PB and PF1100 Series



107TN221

Red (OFF) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS



107TN222

Turquoise (ON) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS