

Plug-In Timer - Digital Astronomic Landscape Timer

Item DT200LT



PRODUCT DESCRIPTION

Digital 24-hour landscape timer with DST, rated for use in low voltage transformers up to 1200W featuring ON programming at Dusk or predetermined time and OFF at Dawn or predetermined time.

FEATURES

- For use in low voltage transformers up to 1200 W
- Program ON at dusk or specific time
- Program OFF at dawn or specific time
- Automatic Daylight Savings Time adjustment
- Intermatic Linesync timing technology for years of accurate timing

APPLICATIONS

- Indoor Lighting Control
- Outdoor Lighting Control
- Landscape Water Control

TECHNICAL DATA

General

| | |
|--------------------------------|------------------------------------|
| Model Number | DT200LT |
| Description | Digital Astronomic Landscape Timer |
| UPC Code | 078275148901 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 1-Year limited |
| TARIC HS Code | 9107.00.00 |

Control Specifications

| | |
|--|--|
| Minimum ON/OFF Times | 1 min |
| Maximum ON/OFF Operations | 2 |
| Operation Features | Astronomic |
| Operation Mode | 24 hour |
| Backup Type | Battery |
| Battery Type | LR44 |
| Mechanism Type | Digital/Electrical |
| Application Compatibilities | Incandescent; Fluorescent; HID; LED; CFL |
| Chemical Composition of the Battery Cell | Alkaline |
| Number of Batteries Included | 2 |
| Battery Weight (grams) | 1.95 |
| Number of Lithium-ion Cells in Battery | N/A |
| Number of Lithium Metal Cells in Battery | N/A |
| Watt Hours Per Battery | 0.225 |
| Lithium Content (grams) in Battery | N/A |

Mechanical Specifications

| | |
|---------------------|------|
| Number of Plugs | 2 |
| Plug Configurations | 5-15 |

Dimensions

Product Dimensions (H x W x D) in 3.188 x 3.307 x 2.224 in

Material Specifications

Color Black

Load Ratings

Incandescent Load Ratings 1000 W, 120 VAC, 60 Hz

Inductive 12 A, 120 VAC, 60 Hz

Motor Load Ratings Ranges 1/2 HP, 120 VAC, 60 Hz

Electrical Specifications

Input Voltage Range(s) 120 VAC, 60 Hz

Packaging

Shipping Weight (lbs) 0.509

Unit Carton Dimensions (H x W x L) in 3.375 x 3.375 x 3.062 in

Environmental Specifications

Usage Environments Outdoor

Standards and Certifications

UL Certification cULus

Other Certifications and Compatibilities Title 20; Green Energy

California Proposition 65 None

RoHS Certification X