

Irrigation Timer - Sprinkler/Irrigation Time Switch with 14-Day Skipper

Item T8805P101C / EAN-Code



PRODUCT DESCRIPTION

These irrigation timers are designed to permit one to 44 "ON" operations every 24 hours and provide watering increments down to 12 minutes or up to 20 hours and 45 minutes to ensure proper watering increments. These models also allow for biweekly scheduling with the convenient 14-day skipper for maximum water conservation and odd/even day compliance.

FEATURES

- ▶ Up to 44 ON/OFF settings per day
- ▶ Water metering increments from 12 minutes to 20 hours and 45 minutes
- ▶ 14-Day skipper enables irrigation to be omitted on selected day(s)
- ▶ Provides for every other day operation
- ▶ ON/OFF/AUTO switch enables shutdown during rainy days and extended watering during dry periods without disturbing the cycle set on dial
- ▶ Type 3R plastic indoor/outdoor enclosure
- ▶ Up to 44 ON/OFF settings per day
- ▶ Water metering increments from 12 minutes to 20 hours and 45 minutes
- ▶ 14-Day skipper enables irrigation to be omitted on selected day(s)
- ▶ Provides for every other day operation
- ▶ ON/OFF/AUTO switch enables shutdown during rainy days and extended watering during dry periods without disturbing the cycle set on dial
- ▶ Type 3R plastic indoor/outdoor enclosure

[[ProductFamilyFeatures9]]

APPLICATIONS

- ▶ Agriculture Feeders
- ▶ Greenhouse Misting Control
- ▶ Water Heater Control

TECHNICAL DATA

Dimensions	
Product Width (in)	6.5
Control Specifications	
Minimum ON/OFF Times	12 min
Maximum ON/OFF Times	20 hours, 45 minutes
Maximum ON/OFF Operations	44
Tripper Actuating Time	12 min
Mechanism Type	Analog/Mechanical
Electrical Specifications	
Switch Type	SPST
Load Voltage	125 VAC, 60 Hz
Amps Per Pole	15 A
HP	1/2
Environmental Specifications	
Temperature (operation)	-40°C..54°C

General

Model Number	T8805P101C
Description	Sprinkler/Irrigation Time Switch with 14-Day Skipper
UPC Code	078275700758
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty	1-Year limited
Feature 1	Up to 44 ON/OFF settings per day
Feature 2	Water metering increments from 12 minutes to 20 hours and 45 minutes
Feature 3	14-Day skipper enables irrigation to be omitted on selected day(s)
Feature 4	Provides for every other day operation
Feature 5	ON/OFF/AUTO switch enables shutdown during rainy days and extended watering during dry periods without disturbing the cycle set on dial
Feature 6	Type 3R plastic indoor/outdoor enclosure

Load Ratings

Motor	1/2 HP, 120 VAC, 60 Hz
Clock Motor Voltage	125 VAC, 60 Hz

Mechanical Specifications

Enclosure Type	Indoor/outdoor type 3R plastic
Number of Trippers Included	12

Packaging

Shipping Weight (lbs)	2.75
Unit Carton Height (in)	4.251
Units Per Pallet	144

Standards and Certifications

CSA Certification	cCSAus
California Proposition 65	Lead
PDF Standards And Certifications	cCSAus
EPI Certifications	cCSAus


ACCESSORIES



156T1950A
Set of 12 Trippers for T1900, T2000, C8800, R8800 and T8800 Series



133T700A
Micro Switch for T8800 and R8800 Series



156T1954A
14 Skipper Pins for R8800, and T8800 Series